

[Home](#) > [Tractors](#) > [5 Family Utility Tractors](#) > [5715 5715 Utility Tractor](#)



5715

5715 Utility Tractor

- 90 Hp Engine with four-wheel drive
- 9F/3R transmission
- Open operator System
- Available Market: Thailand, Cambodia, Indonesia, Malaysia, Philippines, Myanmar, Vietnam

[Locate a Dealer](#)

[View Product Brochure](#) >

Specs & Compare

Key Specifications	
Engine John Deere	John Deere PowerTech 4 Cyclinder Engine, 2100RPM
Horsepower	89 hp (66.4kW)
Transmission	9F, 3R Collar Shift
Engine	
Type (Tier 0)	4045TP066
Aspiration (Tier 0)	Turbocharged
Engine Power @ 2400 rpm (Tier 0)	89 hp (66.4 kW)
PTO Power @ 2400 rpm (Tier 0)	77 hp (57.4 kW)
Maximum Torque (Tier 0)	317 N.m
Cylinders	4
Displacement	4.5 L (278 cu .in3)
Compression ratio (Tier 0)	17.0:1
Bore and Stroke	106.5 x 127 mm (4.19 x 5.00 in.)
Transmission	
Standard	Standard - Top shaft Synchronized 9F/3R Synchronization - All Speeds 1st, 2nd & 4rd
Auxiliary Brake	Parking Pawl
Clutch	
Type	Dry
PTO	

Type	Fully Independent, 540 rpm
PTO Speed	2400 rpm
Size	280 mm (11 in.)

Hydraulic System

Types	Open Center
Pump	Tandem Gear
Flow Rate	Steering - 24.9 L/min (6.6 gpm) Implement - 60.2 L/min (15.9 gpm)
Hitch Load Capacity @ 610	1530 kg (3374 lb)
Category	I & II
Sensor	Draft Links with interchangeable balls

Steering

Type	Hydrostatic
------	-------------

Brakes

Type	Hydraulically Activated Wet Disk
------	----------------------------------

Electrical System

Type	12V Negative Ground
Battery	12V Cold Cranking Ams 550
Alternator	70 A

Capacities

Fuel Tank

Fuel Tank - 95 L (25 U.S. gal.)
Front - 7.5 x 16.0
Front (Optional) - 10.0 x 16.0
Rear - 15.5 x 38
Rear (Optional) - 18.4 x 30

Engine Cooling System

Engine Cooling System - 10.8 L (11.4 U.S. qt)
Front - 13.6 x 24
Front (Optional) - 12.4 x 24
Rear - 15.5 x 38
Rear (Optional) - 18.4 x 30
Rear (Optional) - 18.4 x 30 (casting hub)

Crankcase (including filter)

8.5 L (9 U.S. qt.)

Transmission/Hydraulic

41.8 L (11 U.S. gal.)

Dimensions

Wheelbase

2180 mm (85.8 in)

Total length (including draft

3570 mm (140.5 in.)

Overall width (outside edge

2100 mm (82.6 in.)

Front axle crop clearance

420 mm (16.5 in.)

Height to top of drawbar

513 mm (20.1 in.)

Estimated shipping weight

2687 kg (5923.9 lb)

Tires

Standard front tires

Standard front tires - 13.6 x 24 8PR R1
Optional front tires - 11.2 x 24 8PR R1
Optional front tires - 12.4 x 24 8PR R1

Standard rear tires

Optional rear tires - 16.9 x 30 6PR R1
Optional rear tires - 18.4 x 30 8PR R1
Optional rear tires - 18.4 x 30 10PR R2

Basic Equipment

Water bowl separator

Seat belt

Rops

One selective control valve

Foot throttle

SMV Emblem

Two front and one rear
working lights

Rear brake lights

7 Pin connector

Front weight support

Operators manual

Optional Equipment

Front fenders (MFWD)

Toolbox

Deluxe canopy

2nd Rear Selective Control Valve

2 Function Joystic with mid valve

Seat armrest

Horn

Show Less

Shop and Buy

Contact a Dealer

Maintenance and Support

Parts

Manuals and Training

Equipment models, features, options, attachments and prices may vary in different locations. Please contact your local John Deere dealer for details. John Deere has the sole discretion to review and adjust the specifications, model features and prices of John Deere parts. Before operating the vehicle, you are required to carefully read and strictly follow the safety instructions provided in any product/operator/service manual for the vehicle.

Actual vehicle top speed may vary based on belt wear, tire selection, vehicle weight, fuel condition, terrain and other environmental factors. The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Variation may exist between the actual operation data and defaulted data for the horsepower and torque. Please refer to the original engine manufacturer’s website for detailed information. Optional accessories and attachments are not included in the standard warranty claim for reimbursement. The product (including its components) and accessories may not be available in all regions.